



SECURE UPS 3000VA

SECURE UPS-3000VA Specifications

Input Voltage:	220VAC
Frequency:	50hz – 60hz
Output Voltage:	220VAC
Capacity VA/Wattage:	3000VA/1800W
Power Cord Length:	1.2meter
Outlet Socket:	back-up x5 / bypass x1, total of 6 sockets
Plug & Socket:	NEMA 5-15p & NEMA 5-15r
Transfer Time:	≤10ms including direction time
Wave Form:	Sine wave under main supply, square wave under battery operation
Protection:	Overload. As load over 130%, UPS is protected in 3seconds. Load input. Fuse for overload and short circuit protection. <u>Short Circuit.</u> UPS cut off immediately.
Battery:	Type: <u>Sealed lead acid maintenance-free.</u> <u>Protection.</u> Auto-inspection, discharge protection and battery fault caution.
<u>Battery.</u>	Normally, battery is charge once in three months, it is less than 6hours charging a time.
<u>Audible Alarm:</u>	Battery Mode.
<u>Sufficient battery capacity,</u>	buzzer rings every 4seconds, red light flash.
<u>Insufficient battery capacity,</u>	buzzer rings every 1second, red light flashing.
<u>Battery Low Voltage or Overload/Short Circuit:</u>	Buzzer keeps ringing, red light on.
Physical:	<u>Weight(kg):</u> 11.5kg <u>Size (LxWxH) mm:</u> 400x142x210

